

Technical sheet :

MT 625 HA



Capacities		Metric
Max. capacity	Q	2500 kg
Max. lifting height	h3	5.85 m
Breakout force with bucket (daN)		3427
Weight and dimensions		
Overall length to carriage	l11	3.9 m
Overall length (with forks)	l1	3.9 m
Overall width	b1	1.81 m
Overall height	h17	1.92 m
Wheelbase	y	2.3 mm
Ground clearance	m4	0.33 m
Overall cab width	b4	0.79 m
Outer turning radius	Wa3	3.31 m
External turning radius (over tyres)	Wa1	3.31 m
Tyres type		Pneumatic
Forks length / width / section	l / e / s	1200 mm x 125 mm x 45 mm
Frame Levelling Longitudinal +/- (Degree)		0
Performances		
Lifting		7.8 s
Lowering		5.6 s
Extension		5.4 s
Retraction		3.5 s
Scoop		3 s
Crowd		3 s
Dump		3 s
Engine		
Engine brand		Kubota
Engine norm		Stage V
Engine model		V3307-DI-T-E4B
Capacity of cylinders		3331 cm ³
I.C. Engine power rating (hp)		75
Max. torque		265
Drawbar pull (Laden)		3550
Transmission		
Transmission type		Hydrostatic
Number of gears (forward)		2
Travel speed (laden)		24.9 km/h
Parking brake		Automatic Negative Hand-brake
Hydraulics		
Pump Type		Gear pump
Hydraulic flow / Pressure		90 / 235 Bar
Tank capacities		
Engine oil		11.2 l
Hydraulic oil		115 l
Fuel tank		63 l
Noise and vibration		
Noise at driving position (LpA)		76 dB(A)
Noise to environment (LWA)		104 dB(A)
Vibration on hands/arms		0 Nm
Compatible platform		
Platform dimensions (length)	lp	0 m
Platform weight*		4800 kg
Miscellaneous		
Steering wheels (front / rear)		2 / 2
Drive wheels (front / rear)		2 / 2
Safety cabin homologation		Cab ROPS - FOPS Level 2
Controls		JSM

Dimensional drawing





Siège Social

430 rue de l'Aubinière - 44150 Ancenis Cedex - France

Tel: +33(0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This brochure describes versions and configuration options for Manitou products which may be fitted with different equipment. The equipment described in this brochure may be standard, optional or not available depending on version. Manitou reserves the right to change the specifications shown and described at any time and without prior warning. The manufacturer is not liable for the specifications given. For more information, contact your Manitou dealer. Non-contractual document. Product descriptions may differ from actual products. List of specifications is not comprehensive. The logos and visual identity of the company are the property of Manitou and may not be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are provided for information only.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,547,824 euros - 857 802 508
RCS Nantes